

Technické parametre Showin

MODEL	Zaťaženie	Krútiaci moment	Rýchlosť	Napájanie	Výkon	Príkon	Pracovný čas	Ochrana	Dĺžka
	kg	Nm	Ot/min	V/Hz	W	A	min	IP	mm
MS35SM06H0B00	17	6	28	230/50	121	0,53	4	44	440
MS35SM10H0B00	27	10	17	230/50	121	0,53	4	44	440
MS45SM10H0B00	20	10	15	230/50	140	0,49	4	44	450
MS45SM20H0B00	35	20	15	230/50	150	0,64	4	44	450
MS45SM30H0B00	55	30	15	230/50	180	0,83	4	44	480
MS45SM40H0B00	80	40	15	230/50	240	0,86	4	44	500
MS45SM50H0B00	95	50	12	230/50	240	0,89	4	44	500
MS45MM20H0B00	35	20	15	230/50	150	0,64	4	44	520
MS45MM30H0B00	55	30	15	230/50	180	0,83	4	44	580
MS45MM40H0B00	80	40	15	230/50	240	0,86	4	44	580
MS45MM50H0B00	95	50	12	230/50	240	0,89	4	44	580
MS59SM80H0B00	125	80	18	230/50	330	1,43	4	44	585
MS59SM0AH0B00	165	100	9	230/50	340	1,52	4	44	585
MS59MM80H0B00	125	80	15	230/50	330	1,43	4	44	695
MS59MM0AH0B00	165	100	9	230/50	340	1,52	4	44	695